

Distinctive Process **SUTTER - EPC 50/90**



EPC Pneumatic press Outstanding results to express your difference



The Sutter press is nowadays a worldwide reference especially thanks to its performances, its technology and the high quality of the musts obtained with it.

A gentle pressing process, a large surface of draining and an easy cleaning are the main assets of this slotted-cage press.



Tactile control panel



Sutter EPC 90

Sutter exclusive features

- 400V-50Hz three-phased press.
- Working pressure up to 1.9 Bar.
- Slotted cage (coaxial slots on one half of the cage) in stainless steel in order to facilitate the draining and evacuation of the musts while pressing.
- Very limited production of lees.
- A wear resistant, sealed membrane made in 100% polyurethane. Possibility to press small quantities with no risk for the membrane.
- Lengthwise, sliding doors with a wide opening of 1185 x 420 mm (EPC 50) and of 1185 x 406 mm (EPC 90) for a complete, easy filling and a quick emptying of the pomace.
- Operator safety thanks to a winding cable.
- Axial filling (in option) with a ball valve or knife valve and a highly-accurate safety device that stops automatically the grape pump, diameter of the connection fittings 125 mm.
- Musts are collected in the stainless steel.
- Easier cleaning inside and outside the cage with a water hose.
- 2-way rotation of the cage for an easier handling.
- Very simple tilting dismantling of the doors.

Adapted programming

PLC available through the electronic, tactile, fully automated control panel – Available programming:

- “Filling” programming: based on a dynamic draining.
- “Main Automatic” programming: based on successive, automatic pressing cycles.
- “Specific” programming: based on the setting of each parameter of a pressing cycle.
- “Specific, through training” programming: based on the setting of the pressure steps while the pressing is being carried out.

Technical characteristics

Sutter EPC	Full grapes* (kg)	Destemmed grapes* (kg)	Fermented grapes* (kg)	Nominal power (kW)
50	3250	10000	15000	10,4
90	5850	18000	27000	14

Sutter EPC	Length (mm)	Width (mm)	Height (mm)	Capacity of the trough (L)
50	4860	1966	2310	400
90	5590	2300	2735	600

* As a guide, variable according to vine variety, maturity and filling conditions.



www.sutterag.com
Distinctive Process

Bucher Vaslin
Rue Gaston Bernier – BP 70028
F - 49290 Chalonnes sur Loire
Tél. +33 (0)2 41 74 50 50
Fax +33 (0)2 41 74 50 51
E-mail : commercial@buchervaslin.com